

Issued by	NMi Certin B.V., designated and notified by the Netherlands to perform tasks with respect to conformity modules mentioned in article 9 of Directive 2004/22/EC, after having established that the Measuring instrument meets the applicable requirements of Directive 2004/22/EC, to:																														
Manufacturer	Emerson Process Management Ltd. Logie Court Stirling University Innovation Park Stirling FK9 4NF United Kingdom																														
Measuring instrument	A non-interruptible <b>measuring system</b> installed on a platform.																														
	<table border="0"> <tr> <td style="padding-right: 10px;">Manufacturer</td> <td>:</td> <td>Emerson Process Management Ltd.</td> </tr> <tr> <td>Type</td> <td>:</td> <td>FISCAL OIL EXPORT</td> </tr> <tr> <td><math>Q_{min} - Q_{max}</math></td> <td>:</td> <td>20 – 200 m<sup>3</sup>/h</td> </tr> <tr> <td>MMQ</td> <td>:</td> <td>See paragraph 1.2</td> </tr> <tr> <td>Accuracy class</td> <td>:</td> <td>0.3</td> </tr> <tr> <td>Environment classes</td> <td>:</td> <td>M1 / E2</td> </tr> <tr> <td>Temperature range liquid</td> <td>:</td> <td>-20 °C / +100 °C</td> </tr> <tr> <td>Temperature range ambient</td> <td>:</td> <td>-25 °C / + 55 °C</td> </tr> <tr> <td>Maximum pressure</td> <td>:</td> <td>93 Bar(g)</td> </tr> <tr> <td>Intended for the measurement of</td> <td>:</td> <td>Crude oil with a viscosity around 2 cSt.</td> </tr> </table>	Manufacturer	:	Emerson Process Management Ltd.	Type	:	FISCAL OIL EXPORT	$Q_{min} - Q_{max}$	:	20 – 200 m <sup>3</sup> /h	MMQ	:	See paragraph 1.2	Accuracy class	:	0.3	Environment classes	:	M1 / E2	Temperature range liquid	:	-20 °C / +100 °C	Temperature range ambient	:	-25 °C / + 55 °C	Maximum pressure	:	93 Bar(g)	Intended for the measurement of	:	Crude oil with a viscosity around 2 cSt.
Manufacturer	:	Emerson Process Management Ltd.																													
Type	:	FISCAL OIL EXPORT																													
$Q_{min} - Q_{max}$	:	20 – 200 m <sup>3</sup> /h																													
MMQ	:	See paragraph 1.2																													
Accuracy class	:	0.3																													
Environment classes	:	M1 / E2																													
Temperature range liquid	:	-20 °C / +100 °C																													
Temperature range ambient	:	-25 °C / + 55 °C																													
Maximum pressure	:	93 Bar(g)																													
Intended for the measurement of	:	Crude oil with a viscosity around 2 cSt.																													
	<p>Further properties are described in the annexes:</p> <ul style="list-style-type: none"> <li>- Description T10571 revision 0;</li> <li>- Documentation folder T10571-1.</li> </ul>																														
Valid until	8 July 2023																														

Issuing Authority **NMi Certin B.V., Notified Body number 0122**  
 8 July 2013

**C. Oosterman**  
 Head Certification Board

**NMi Certin BV**  
 Hugo de Grootplein 1  
 3314 EG Dordrecht  
 PO Box 394  
 3300 AJ Dordrecht, NL  
 T +31 78 6332332  
 F +31 78 6332309  
 certin@nmi.nl  
 www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The designation of NMi Certin B.V. as Notified Body can be verified at <http://ec.europa.eu/enterprise/newapproach/nando>

Parties concerned can lodge objection against this decision, within six weeks after the date of submission, to the general manager of NMi (see [www.nmi.nl](http://www.nmi.nl))

Reproduction of the complete document is permitted.